

## CLAIMS

1. A multicarrier transmitting apparatus comprising:  
a dividing section that divides transmit data into  
5 high-quality transmit data for which good quality is  
required and ordinary transmit data other than said  
high-quality transmit data;  
a rearranging section that rearranges said transmit  
data so that said high-quality transmit data is allocated  
10 to a subcarrier in the vicinity of a center frequency;  
and  
an orthogonal frequency division multiplexing  
section that performs orthogonal frequency division  
multiplexing of said transmit data rearranged by said  
15 rearranging section and allocates said transmit data to  
subcarriers.
2. The multicarrier transmitting apparatus according  
to claim 1, further comprising a spreading section that  
20 performs spreading processing of said transmit data  
rearranged by said rearranging section, wherein said  
orthogonal frequency division multiplexing section  
performs orthogonal frequency division multiplexing of  
said transmit data that has undergone spreading  
25 processing and allocates said transmit data to  
subcarriers.
3. The multicarrier transmitting apparatus according

to claim 2, wherein said spreading section independently sets spreading ratios of said high-quality transmit data and said ordinary transmit data.

- 5    4.    The multicarrier transmitting apparatus according to claim 2, wherein said spreading section makes a spreading ratio of said high-quality transmit data greater than a spreading ratio of said ordinary transmit data.

10

5.    The multicarrier transmitting apparatus according to claim 2, wherein code multiplexing numbers of said high-quality transmit data and said ordinary transmit data are set independently.

15

6.    The multicarrier transmitting apparatus according to claim 2, wherein a code multiplexing number of said high-quality transmit data is made smaller than a code multiplexing number of said ordinary transmit data.

20

7.    The multicarrier transmitting apparatus according to claim 2, wherein numbers of spreading codes assigned to said high-quality transmit data and said ordinary transmit data are set independently.

25

8.    The multicarrier transmitting apparatus according to claim 2, wherein a number of spreading codes assigned to said high-quality transmit data is made greater than

a number of spreading codes assigned to said ordinary transmit data.

9. The multicarrier transmitting apparatus according to claim 1, further comprising a modulation section that modulates said high-quality transmit data and said ordinary transmit data using independently set modulation methods.

10. The multicarrier transmitting apparatus according to claim 9, wherein said modulation section fixes a modulation method of either said high-quality transmit data or said ordinary transmit data, and adaptively changes a modulation method of the other of said high-quality transmit data or said ordinary transmit data.

11. The multicarrier transmitting apparatus according to claim 9, wherein said modulation section adaptively changes a modulation method of both said high-quality transmit data and said ordinary transmit data.

12. The multicarrier transmitting apparatus according to claim 9, wherein said modulation section selects a modulation method in accordance with an adjacent channel interference wave reception level.

13. The multicarrier transmitting apparatus according

to claim 1, further comprising an interleaving section that independently interleaves said high-quality transmit data and said ordinary transmit data, wherein said rearranging section rearranges said transmit data  
5 after interleaving.

14. The multicarrier transmitting apparatus according to claim 1, wherein said rearranging section rearranges said transmit data so that said ordinary transmit data  
10 is allocated to a subcarrier containing a DC point.

15. The multicarrier transmitting apparatus according to claim 1, further comprising a transmission power setting section that sets transmission power of said  
15 high-quality transmit data higher than transmission power of said ordinary transmit data.

16. The multicarrier transmitting apparatus according to claim 15, wherein said transmission power setting  
20 section sets transmission power of said high-quality transmit data and said ordinary transmit data variably.

17. The multicarrier transmitting apparatus according to claim 15, wherein said transmission power setting  
25 section sets transmission power of either said high-quality transmit data or said ordinary transmit data variably.

18. The multicarrier transmitting apparatus according to claim 15, wherein said transmission power setting section varies transmission power in accordance with channel quality.

5

19. The multicarrier transmitting apparatus according to claim 1, wherein said orthogonal frequency division multiplexing section narrows a range of subcarriers to which said high-quality transmit data is allocated when  
10 an adjacent channel interference wave reception level increases.

20. The multicarrier transmitting apparatus according to claim 1, further comprising a coding section that  
15 turbo-codes said transmit data, wherein said high-quality transmit data is systematic bit data and said ordinary transmit data is parity bit data.

21. The multicarrier transmitting apparatus according to claim 1, wherein said high-quality transmit data is  
20 transmit data that is transmitted to a distant communicating party, and said ordinary transmit data is transmit data that is transmitted to a nearby communicating party.

25

22. The multicarrier transmitting apparatus according to claim 1, wherein said high-quality transmit data is information used for communication control or

retransmission information.

23. The multicarrier transmitting apparatus according to claim 1, further comprising a selection section that  
5 selects said ordinary transmit data so that subcarriers to which part of said ordinary transmit data rearranged by said rearranging section and said high-quality transmit data are allocated are transmitted.

10 24. The multicarrier transmitting apparatus according to claim 1, wherein said selection section selects said ordinary transmit data so that a number of subcarriers to which said ordinary transmit data is allocated that are transmitted is variable.

15

25. The multicarrier transmitting apparatus according to claim 1, wherein said selection section selects said ordinary transmit data so that a number of subcarriers to which said ordinary transmit data is allocated that  
20 are transmitted is variable according to channel quality.

26. The multicarrier transmitting apparatus according to claim 1, wherein said selection section selects said ordinary transmit data so that a number of subcarriers  
25 to which said ordinary transmit data is allocated that are transmitted is variable based on delay distribution information of said transmit data.

27. The multicarrier transmitting apparatus according to claim 1, wherein said selection section selects said ordinary transmit data that is allocated to subcarriers of a predetermined reception level or higher.

5

28. The multicarrier transmitting apparatus according to claim 1, wherein said selection section selects so that a number of subcarriers to which said ordinary transmit data is allocated that are transmitted is  
10 variable in accordance with an adjacent channel interference wave reception level.

29. A base station apparatus that has a multicarrier transmitting apparatus comprising:

15 a dividing section that divides transmit data into high-quality transmit data for which good quality is required and ordinary transmit data other than said high-quality transmit data;

a rearranging section that rearranges said transmit  
20 data so that said high-quality transmit data is allocated to a subcarrier in the vicinity of a center frequency; and

an orthogonal frequency division multiplexing section that performs orthogonal frequency division  
25 multiplexing of said transmit data rearranged by said rearranging section and allocates said transmit data to subcarriers.

30. A communication terminal apparatus that has a multicarrier transmitting apparatus comprising:

5 a dividing section that divides transmit data into high-quality transmit data for which good quality is required and ordinary transmit data other than said high-quality transmit data;

10 a rearranging section that rearranges said transmit data so that said high-quality transmit data is allocated to a subcarrier in the vicinity of a center frequency; and

an orthogonal frequency division multiplexing section that performs orthogonal frequency division multiplexing of said transmit data rearranged by said rearranging section and allocates said transmit data to subcarriers.

31. A multicarrier transmitting method comprising:

20 a step of dividing transmit data into high-quality transmit data for which good quality is required and ordinary transmit data other than said high-quality transmit data;

a step of rearranging said transmit data so that said high-quality transmit data is allocated to a subcarrier in the vicinity of a center frequency; and

25 a step of performing orthogonal frequency division multiplexing of rearranged said transmit data and allocating said transmit data to subcarriers.



32. The multicarrier transmitting method according to claim 31, further comprising a step of spreading said transmit data.

5 33. The multicarrier transmitting method according to claim 31, further comprising a step of modulating said high-quality transmit data and said ordinary transmit data using independently set modulation methods.

10 34. The multicarrier transmitting method according to claim 33, further comprising a step of selecting a modulation method in accordance with an adjacent channel interference wave reception level.

15 35. The multicarrier transmitting method according to claim 31, wherein said high-quality transmit data is transmit data that is transmitted to a distant communicating party, and said ordinary transmit data is transmit data that is transmitted to a nearby  
20 communicating party.

36. The multicarrier transmitting method according to claim 31, further comprising a step of independently interleaving said high-quality transmit data and said  
25 ordinary transmit data.

37. The multicarrier transmitting method according to claim 31, wherein said ordinary transmit data is selected

so that subcarriers to which part of said ordinary transmit data rearranged by said rearranging section and said high-quality transmit data are allocated are transmitted.